Proxima DP6860 Projector
Technical and Functional Specifications

Native Resolution	• XGA (1024 x 768)
Display Technology	• 3 x 1.3" polysilicon TFTs
Input Sources	• Computer: HD15 x 2 (Analog RGB), DVI-D, audio x 2 (3.5mm stereo mini jack); Video: RCA x 3 (RGB Component, YPbPr, YCbCr), S-Video, Composite Video, Audio (RCA x 2)
Output Sources	• RGB (HD15), audio (3.5mm stereo mini-jack)
Computer Compatibility	• SXGA, XGA, SVGA, VGA, Mac
Video Compatibility	• NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM
Brightness	• 2400 ANSI lumens
Brightness Uniformity	• 85%
Contrast Ratio	• 260:1 full on/full off
Number of Colors	• 16.7 million
Image Size	• 762 mm - 7620 mm (diagonal)
H-Sync Range	• 31.5 - 80 kHz
V-Sync Range	• 56 - 120 Hz
Digital Keystone Correction	• +/- 30 degrees
Projection Lens	• F = 1.7 - 2.3; f = 49 - 64 mm
Minimum Projection Distance	• 1.1 m (standard lens)
Aspect Ratio	• Native 4:3; Supports 5:4, 16:9
Throw Ratio	• 1.8:1 to 2.4:1 (image width: throw dist.)
Projection Method	• Front, rear and ceiling
Audio	• 2 x 1.2 Watt stereo
Lamp	• 250 Watt UHB
Dimensions	• 289 mm (W) x 119 mm (H) x 345 mm (L)
Weight	• 14.1 lbs. (6.4 kg)
Power Consumption	• 400 Watts
Operating Temperature	• 5 - 35° C
On-Screen Menu Languages	• English, French, German, Spanish, Italian, Norwegian, Dutch, Portuguese
Audible Noise	• Less than 40dB
Approvals	• UL, cUL, CE, FCC Class A, TUV, C-tick, NOM, IRAM
Warranty	• Two years on parts and labor (excluding lamp)
	• 90-day or 500 hour lamp warranty

Copyright © 1997-2004 InFocus Corporation.
All Rights Reserved.